543 EUROSAFE DECO

High quality adhesive for the installation of PVC strips and tiles.

Product Typification

Basis	:	Acrylic dispersion.
Colour	:	Light blue.
Consistency	:	liquid.

- Non-flammable
- Roller-castor-chair resistant
- Favourable spreading capacity
- No grin through of adhesive trowel marks
- Easy and safe to apply
- High final bond strength

Performances

Specific weight	:	1.04 kg/l.
Consumption	:	100-150 g/m², on levelled subfloors.

Application

For the installation of PVC strips and tiles on levelled subfloors.

Working Process

Storage	:	Store cool and free from frost. Protect against high temperatures.
Tools	:	Lambswool roller or brush.
Latency	:	None.
Drying time	:	24 hours.*
Shelf Life	:	12 months, in unopened packaging.
Cleaner	:	Water.

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- 543 Eurosafe Deco is suitable for any type of subfloor that has good tensile and compression strength. The subfloor should also be even, clean, permanently dry and free from grease and dirt according to the requirements of BS 8203 or DIN 18 365.
- Anhydrite floors should be sandpapered. Thereafter make the floor dust free and prime with 044 Europrimer Multi. This layer has to dry sufficiently.

- For an optimal final result, apply a 2 mm levelling compound layer on the subfloor.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

Working conditions:

Required surrounding temperature : 18º - 23ºC
Temperature for material and subfloor : min. 15º - max. 20º C.
Relative humidity : 40-80%.

Directions for use:

- It is very important to acclimatize the PVC-material for at least 48 hours in the room where it will be installed.
- Apply 543 Eurosafe Deco equally (well covered) in the recommended quantity with a lambswool roller or brush on the subfloor.
- The strips or tiles can be placed directly into the wet, semi moist or dry adhesive.
- Drying time is depending on temperature, relative humidity and the porosity of the subfloor.
- After applying carefully roll and firmly rub the strips or tiles in to the adhesive line.
- Drying time minimal 24 hours.
- Remove fresh adhesive spots immediately with a clean damp cloth.

Underfloor heating systems:

543 Eurosafe Deco can be applied on underfloor heating systems. The startprotocol of the floorheating needs to be completly executed in accordance with the directives of the supplier. Turn off the heater 24 hours before fixation. Do not heat again until at least 24 hours after fixation, in steps of maximum 5° C water temperature per day. If there is the possibility that he PVC- strips or tiles can be warmer than 30 °C (also by sunlight), you have to choose for a polyurethane bonding.

Environment and health

Hazard Class	:	None.
Safety and environment	:	Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.
MSDS	:	Available on request.

Articles

Article	Definition	Packaging	EAN-code
543	Eurosafe Deco	10 kg bucket.	8 710345 543002